

Spectral Gamma-Ray Borehole Log Data Report

Page 1 of 2

Log Event A

Borehole 30-01-12

Borehole Information

Farm : \underline{C} Tank : $\underline{C-101}$ Site Number : $\underline{299-E27-61}$

N-Coord: 42,762 W-Coord: 48,339 TOC Elevation: 646.82

Water Level, ft : Date Drilled : $\frac{3/31/1970}{}$

Casing Record

Type: Steel-welded Thickness: 0.280 ID, in.: 6

Top Depth, ft. : $\underline{0}$ Bottom Depth, ft. : $\underline{100}$

Borehole Notes:

This borehole was drilled in March 1970 and completed to a depth of 100 ft with 6-in. casing. The casing thickness is presumed to be 0.280 in., on the basis of the published thickness for schedule-40, 6-in. steel tubing. No information was available that indicated the borehole was perforated or grouted; therefore, it is assumed that the borehole was not perforated or grouted. The top of the casing, which is the zero reference for the SGLS, is 6 in. above the tank farm ground surface.

Equipment Information

 Logging System :
 2
 Detector Type :
 HPGe
 Detector Efficiency:
 35.0 %

 Calibration Date :
 10/1996
 Calibration Reference :
 GJO-HAN-13
 Logging Procedure : P-GJPO-1783

Log Run Information

 Log Run Number :
 1
 Log Run Date :
 03/20/1997
 Logging Engineer:
 Bob Spatz

 Start Depth, ft.:
 0.0
 Counting Time, sec.:
 100
 L/R : I
 Shield : N

Finish Depth, ft.: 0.0 Counting Time, sec.: 100 L/R: L Shield: N Finish Depth, ft.: 18.0 MSA Interval, ft.: 0.5 Log Speed, ft/min.: N

Log Run Number: 2 Log Run Date: 03/21/1997 Logging Engineer: Bob Spatz

Start Depth, ft.: $\underline{99.5}$ Counting Time, sec.: $\underline{100}$ L/R: \underline{L} Shield: \underline{N} Finish Depth, ft.: $\underline{17.0}$ MSA Interval, ft.: $\underline{0.5}$ Log Speed, ft/min.: $\underline{n/a}$



Spectral Gamma-Ray Borehole Log Data Report

Page 2 of 2

Borehole 30-01-12

Log Event A

Analysis Information

Analyst: D.L. Parker

Data Processing Reference : P-GJPO-1787 Analysis Date : 06/27/1997

Analysis Notes:

This borehole was logged by the SGLS in two log runs. The pre- and post-survey field verification spectra met the acceptance criteria established for the peak shape and detector efficiency, confirming that the SGLS was operating within specifications. The energy calibration and peak-shape calibration from these spectra were used to establish the peak resolution and channel-to-energy parameters used in processing the spectra acquired during the logging operation. There were no fine gain adjustments made during these log runs.

Casing correction factors for a 0.280-in.-thick steel casing were applied during analysis.

The man-made radionuclide Cs-137 was detected in this borehole. The Cs-137 contamination was detected nearly continuously from the ground surface to a depth of 40.5 ft. Isolated occurrences of Cs-137 were detected at 45, 60, and 66.5 ft, and at the bottom of the logged interval (99.5 ft).

The U-238 concentration data are almost entirely absent from the ground surface to 8 ft.

The K-40 concentrations increase to about 14 pCi/g between 38.5 and 50.5 ft. K-40 concentrations are slightly decreased from 51 to about 58 ft. The K-40 background concentrations increase gradually from 59.5 to 92.5 ft.

Additional information and interpretations of log data are included in the main body of the Tank Summary Data Reports for tanks C-101 and C-104.

Log Plot Notes:

Separate log plots show the man-made and the naturally occurring radionuclides. The natural radionuclides can be used for lithology interpretations. The headings of the plots identify the specific gamma rays used to calculate the concentrations. Uncertainty bars on the plots show the statistical uncertainties for the measurements as 95-percent confidence intervals. Open circles on the plots give the MDL. The MDL of a radionuclide represents the lowest concentration at which positive identification of a gamma-ray peak is statistically defensible.

A combination plot includes the man-made and natural radionuclides, the total gamma derived from the spectral data, and the Tank Farms gross gamma log. The gross gamma plot displays the latest available digital data. No attempt has been made to adjust the depths of the gross gamma logs to coincide with the SGLS data.